

By email to: planning.policy@stalbans.gov.uk

Local Plans team
St Albans City & District Council
Civic Centre
St Peter's Street
St Albans
Hertfordshire, AL1 3JE

8 August 2025 My Ref: 23/315

Dear sir/madam,

RE: ST ALBANS LOCAL PLAN EXAMINATION 2025 – ADDITIONAL DOCUMENTS CONSULTATION SADC/ED77 – FLOOD RISK ADDENDUM
SITE M20 – LAND AT LOWER LUTON ROAD, HARPENDEN

Thank you for the opportunity to comment on the additional documents published on 4 July 2025. I write in response to the Flood Risk Addendum, ref SADC/ED77, and specifically in relation to groundwater flooding.

As you are aware, DLA Town Planning acts for Jarvis Homes, who are the promoters of Land at Lower Luton Road – proposed housing allocation M20 in the submitted draft Local Plan. Jarvis Homes are working with the landowners to bring forward a residential development on the site and you may have seen the recent pre-application submission we made, seeking the Council's comments on our emerging layout.

Paragraph 3.3.2 of the Council's Strategic Flood Risk Assessment (SFRA) Level 1 addendum published in 2024 highlights that limited information is available on groundwater flooding. The lack of available data means that it is not possible to provide an equivalent level of analysis to that provided for river flooding, for example. While the Council's consultants have done their best to fill the void, Appendix B for the SFRA Level 1 Addendum highlights the caveats that come with their work:

"Due to the limitations of this dataset, it could not be used with confidence unless supported by more detailed local studies. The mapping provides an indication of where risk might be higher, but it would not be easy to defend sequential decisions based on the available mapping." (SFRA Level 1 addendum, Appendix B).

This heightened level of uncertainty is important. It is not appropriate, at this stage, for the Local Plan to specify the impact that groundwater flooding might have on development capacity, given the paucity of information. The estimates of capacity given for each proposed allocation are "indicative", so sufficient flexibility exists to vary capacity at a later stage.



We therefore object to the proposed reduction in capacity for site M20 from 25 to 12. The data does not support this reduction and is not sufficiently detailed to be reliable.

In contrast, Jarvis Homes are monitoring <u>actual</u> groundwater levels at the site through the installation of boreholes. The initial results are attached at Appendix A to this letter and are summarised by Infrastruct Consulting Civil Engineers. As can be seen, in July 2025 groundwater was encountered at just over 1m below ground level, which contrasts with the modelled results relied upon by the Council of 0 to 0.025m below ground level. We acknowledge these results are only a snapshot and Jarvis Homes will continue to monitor groundwater levels to establish any seasonal variations. However, at this stage, the evidence does not support the proposed reduction in development capacity.

A detailed Flood Risk Assessment will be required with any planning application and this would be the point at which the detailed impact of any groundwater flood risk will become clear. The capacity of the site can be established at that time.

The SFRA Level 2 Addendum sets out a number of potential mitigation measures that should be considered. These are listed below with some initial commentary:

- Raising finished floor levels as set out in Appendix A, finished floor levels will be higher than surrounding levels.
- Avoiding basements no basements are proposed or envisaged.
- Potential limitations in the use of infiltration may mean SuDS features need to be larger –
 Jarvis Homes control a larger area of land beyond the proposed allocation (as set out in our
 Regulation 19 representations). If groundwater levels mean larger SuDS features are
 necessary, these can be accommodated elsewhere on the site, outside of the development
 area.

The proposed policy for site M20 should remain as per the submitted draft Local Plan.

We look forward to discussing this site with the Inspectors at the forthcoming hearing session. If there are any questions in the meantime, please feel free to contact me.

Yours faithfully



Simon Andrews Strategic Planning Manager

Appendix A – Infrastruct CS Ltd response and Geo-site Assessment (WDE Consulting)



Infrastruct CS Ltd The Stables, High Cogges Farm, High Cogges, Witney, Oxon, OX29 6UN Tel: 01993 709709

Email: info@infrastructcs.co.uk Web: www.infrastructcs.co.uk

28th July 2025

REF: 6017-LUTO-ICS-CO-C-03.003A

Lower Luton Road, Harpenden AL5 5ES (M20 in Draft Local Plan)

This statement has been prepared by Infrastruct CS Ltd to assist the M20 Land Promoter with the assessment of flood risk from different sources, including fluvial, pluvial and groundwater.

In this capacity, we have already assessed the results of some preliminary intrusive ground investigation carried out by WDE Consulting in May 2025 (Report Ref: 21372R1), and that can be found in Appendix A of this document. In there, groundwater was encountered in three different locations at 1.1m below ground level, far from the 0.025mbgl that the JBA Consulting map indicates.

Further testing was carried out by Lucion Ground Engineering Ltd in July 2025, (Report Ref: 136262), in two locations. In WS01, water rose to 1.05mbgl, approximately at 83.35mAOD. In WS02, water remained at 4.20mbgl, approximately at 83.50mAOD.

Based on these findings we believe a scheme close to the one submitted as part of a recent pre-application (See attached in Appendix B) could be feasible from a flood risk and drainage perspective. Especially if 4 of 5 houses are removed to provide a large above ground SuDs feature, and all finished floor levels are at 85.00mAOD or higher.

Extensive earthworks are necessary to provide accessible gradients to all footpaths and roads, and to maintain or even increase the floodplain volumes to the south, giving further protection to adjoining/neighbouring land. Proposed finished floor levels for all units will be higher than the surrounding levels as well. If our current findings are proven to be consistent in the winter, a scheme of approximately 30 dwellings should be achievable, albeit this may reduce once further data is available.

Yours sincerely



M. BLANCO MEng CEng MICE DIRECTOR

Authorised by



A. J. GRIFFITHS
BEng (Hons) MCIHT
DIRECTOR







Appendix A





Geo-Site Assessment Lower Luton Road Harpenden AL5 5AF

Client: Jarvis Strategic Land Ltd

Issue Date: May 2025 Report Ref: 21372R1 (Issue A)















Charlotte Bird

Graduate

May 2025

Consultant

GROUNDED SOLUTIONS

Name

Date

Position

Geo-Site Assessment Lower Luton Road, Harpenden Jarvis Strategic Land Ltd

Simon Ware

May 2025

Managing Director

Corrienne Ainscough

Business Manager

May 2025

Document verification schedule						
Project Name	Lower Luton Road,	Harpenden, AL5 5	AF			
Document title	Geo-Site Assessme	ent				
Document ref	21372R1 (Issue A)					
Date of Issue	May 2025					
Comments	Issued to client					
	Prepared by	Checked by	Quality Check	Approved by		

This report has been prepared in accordance with the scope of WDE Consulting Ltd's (WDE) appointment with the Client for this project and is subject to the terms of the appointment. It includes confidential information for only the Client's benefit and shall not be relied upon or transferred to any third party without the express written authorisation of WDE. If an unauthorised third party comes into possession of this report, they rely on it at their peril and WDE owe them no duty of care and skill.

Jason Fitzgerald

May 2025

Principal Consultant

WDE has prepared this report with reasonable skill, care and diligence in accordance with the current guidance and common practice at the time of issue. It represents a limited assessment which may fail to identify potential hazards outside the agreed areas that have been assessed. Groundwater levels are particularly susceptible to variations due to seasonal or other effects and hence any comments relating to groundwater are limited to the dates they were obtained. The subsurface geological profiles and other plots are generalised by necessity and have been based on the information found at the locations of the exploratory holes and depths sampled and tested. Interpretation of the results contained within this document are based on the proposed site usage and the findings may not be valid should the proposed land use and/or the regulatory regime/guidance change. The findings and opinions conveyed via this document are based on information obtained from a variety of sources as detailed within this report, which WDE Consulting Limited believes are reliable. Nevertheless, WDE Consulting Limited cannot and does not guarantee the authenticity or reliability of the information it has relied upon. In preparing this report, it has been assumed that all past and present occupants have provided all relevant and other information, especially relating to known or potential hazards.

WDE believes that providing information about limitations is essential to help the client identify and thereby manage their risks. These risks can be mitigated, but they cannot be eliminated, through additional assessments. WDE will on request, advise the client of the additional assessment opportunities available, their impact on risk, and their potential cost benefit. It should be noted that WDE does not provide legal advice, and the advice of lawyers may also be required.

The work is also subject to WDE Consulting's standard terms and conditions.



Geo-Site Assessment Lower Luton Road, Harpenden Jarvis Strategic Land Ltd

GROUNDED SOLUTIONS

TAB	LE O	F CON	TENTS	PAGE
1.0	EXE	CUTIVI	E SUMMARY	1
2.0	INT	RODUC	CTION	2
	2.1	CONTE	ехт	2
	2.2	AGREE	D SCOPE OF WORKS AND OBJECTIVES	2
3.0	PHA	ASE 1 D	ESK STUDY	3
	3.1	INFOR	MATION SOURCES	3
	3.2	SITE D	ESCRIPTION AND WALKOVER	3
		3.2.1	Surrounding Area	3
	3.3	KEY FII	NDINGS OF DESK STUDY	3
	3.4	PRELIN	MINARY RISK ASSESSMENT	4
		3.4.1	•	4
		3.4.2		5
		3.4.3		5
		3.4.4	Qualitative Risk Assessment	7
4.0	PHA	ASE II II	NVESTIGATION WORKS	9
	4.1	SUMM	ARY OF WORKS	9
	4.2	CONST	TRAINTS/SELECTION OF INTRUSIVE LOCATIONS	9
	4.3	FIELD I	RESULTS	9
		4.3.1	Geology	9
		4.3.2	Groundwater	9
		4.3.3	Permeability Results	10
		4.3.4	Revised Ground Gas Risk Assessment	10
5.0	REC	OMME	NDATIONS FOR FURTHER WORK	11
TABL				
		_	cope of Works and Objectives	2
		-	ngs of Desk Study	3
			tion of Potential Receptors	5
			tion of Potential Areas of Concern	5
			tion of Potentially Active Human Health Exposure Pathways	6
Table 6 – Identification of Potentially Active Controlled Water Pathways				6 7
Table 7 – Identification of Potentially Active Ground Gas Pathways				
		_	of Potentially Active Source-Pathway-Target Assessment	8
Table	9 – S	ummary	of Geology Proved Onsite	9



Geo-Site Assessment Lower Luton Road, Harpenden Jarvis Strategic Land Ltd

Table 10 – Summary of BRE365 Soakage Testing10Table 11 – Updated Ground Gas Risk Assessment10

FIGURES

Figure 1 – Site Location Plan

Figure 2 – Current Site Plan

Figure 3 – Proposed Site Plan

Figure 4 – Intrusive Location Plan

APPENDIX A

Relevant Guidance and Legislation

APPENDIX B

Site Photos

APPENDIX C

Environmental Database

APPENDIX D

Field Logs

APPENDIX E

Permeability Sheets



1.0 EXECUTIVE SUMMARY

Phase 1 Desk Study	Comments	Risk Rating
Site Setting	Open field used as a garden area and set within curtilage of residential dwelling Forge Cottages	Low
Published Geology and Hydrogeology	 Bedrock geology: Lewes Nodular Chalk Formation and Seaford Chalk Formation (Principal Aquifer, SPZ 3). Superficial geology: Kesgrave Catchment and Alluvium (Secondary A aquifer) 	Moderate
Hydrology/Flood Risk	 River Lea located adjacent S. High risk of flooding. Flood Zone 2 & 3 1no potable abstraction 977m SW 	High
Historical land use	Open field since 1879 until c1980 when Forge Cottages shown. Minor alterations until present day. Surface of Water 18 th February 1922 on 1922 map.	Low
Landfill/Infilled land	 No landfill within 250m of site Sand pit c1922 and c1948 onsite Refuse heap c1922 and c1946 onsite Gravel pit within 20m of site 	Low/moderate
Radon	 Majority of site is within a low risk area (<1%) NW corner within 3-5% risk area requiring basic protection 	Low/moderate
Ground Cavities	Moderate risk areaSolution pipe x 3 located 313m SW	Moderate
ихо	Moderate risk	Moderate
Phase 2 Intrusive	Comments	Risk Rating
Proven Ground Conditions	Topsoil to ~0.20mbgl over gravelly Clay to 1.10mbgl.	
Groundwater/Drainage	 Groundwater encountered at 1.10m bgl. BRE365 soakage value range of 1.07E-05 to 3.64E-06 Moderate/Hig m/sec (moderate/poor to poor) within the gravelly clay. 	
Conclusions and Recommendations • Low/moderate risk from contamination for potential future research to be forwarded to planning • Preliminary UXO assessment to be undertaken • Radon report undertaken for northwest corner		eceptors



2.0 INTRODUCTION

WDE Consulting Limited (WDE) was appointed by Jarvis Strategic Land Ltd (the *client*) to conduct a Geo-Site Assessment at Lower Luton Road, Harpenden, AL5 5AF, What 3 Words ///point.blaze.spoon (Figure 1). The current site comprises an open field within the rear of Forge Cottages, accessed off Crabtree Lane and situated at NGR TL 14920 14908 (Figure 2).

2.1 Context

It is understood that the proposed development comprises the construction of ~22 residential dwellings (Figure 3).

The works have been completed in line with the current regulations, guidance and good practice presented in Appendix \underline{A} .

2.2 Agreed Scope of Works and Objectives

The scope of work that was agreed with the client is presented in Table 1.

Table 1 - Agreed Scope of Works and Objectives

Item	Scope of Works	Objectives
1	Site walkover	To identify any areas of potential contamination
2	Permeability testing	Investigate the drainage potential of the materials through BRE365 permeability testing.
3	Reporting	 Complete a Phase 1 desk-based study of the site to ascertain information on the site geology, hydrology, and surrounding land uses. Provide recommendations on drainage potential.



3.0 PHASE 1 DESK STUDY

3.1 Information Sources

The sources of information that were used during the desk study included the following items:

- Site walkover (photos presented in Appendix B)
- Environmental database information (Appendix C)
- Publicly available information

3.2 Site Description and Walkover

The current site comprises an open field used by the landowners as a private garden and measures ~1.2ha measuring ~120m from north to south and ~100m from west to east and is accessed via a gated entrance off Crabtree Lane.

There were no bulk fuel storage tanks identified onsite, nor any signs of staining to the surface resulting from chemical or oil spillages.

3.2.1 Surrounding Area

The site lies within a semi-rural location comprises the following land uses:

- Northern Boundary: Harpenden Arts and Conference Centre and Katherine Warington School
- Southern Boundary: River Lea and residential dwellings
- Eastern Boundary: Open fields
- Western Boundary: Forge Cottages, with commercial land use further to west

3.3 Key Findings of Desk Study

The key findings from the database information pack are presented in Table 2 with the database presented in full in Appendix C.

Table 2 – Key Findings of Desk Study

Item	Details
Published geology	 Bedrock geology – Lewes Nodular Chalk Formation Superficial geology – Kesgrave Catchment and Alluvium
Geological hazards	 Moderate natural ground subsidence and ground dissolution of soluble rocks All other geological hazards are low
Ground Cavities	Solution pipe x 3 located 313m SW



Geo-Site Assessment Lower Luton Road, Harpenden Jarvis Strategic Land Ltd

GROUNDED SOLUTIONS

Item	Details
Hydrogeology	 Principal Bedrock Aquifer Secondary A Superficial Aquifer SPZ Zone 3 1no potable abstraction 977m SW
Hydrology/flood risk	 River Lea runs along the southern boundary Southern half of site situated within Flood Zone 3 (High Risk) Recorded historical flood events on site from 1947, 1987 and 2007 High surface/groundwater water flood risk
Current land use on site	Open field used as an priavte garden open space area to Forge Cottages
Current land use within 250m	 Sewage pumping station 6m W Harpenden Mill Autocare and Garage 100m W Old Batford Mill 150m W Harpenden Arts and Conference centre 50m N Katherine Warington School 120m N Marquis Lane Allotments 60m SW River Lea Southern site border Residential Dwellings 100m S
Historical land use on site	Open field since 1879 until c1980 when Forge Cottages, with minor alterations until present day. The text <i>Surface of Water 18th February 1922</i> is present on 1922 map.
Historical land use with 250m	 Residential development is present from c1966 (100m S). Further residential expansion appears within 100m of site from c1975 Northwest of site along Lower Luton Road. Batford Mill from c1877 Allotment gardens appear within 100m Southwest of site from c1992 until present Sewage outfall within 200m southeast of site appears c1922 remains until 1993 Sewage works c1877 ~250m south of site, disappears by c1884
Landfills/infilled land Identified potential areas of concern	 No historical landfills within 250m of site Sand pit c1922 and c1948 onsite Refuse heap c1922 and c1946 onsite Gravel pit within 20m of site A: Potentially made ground
Pollution incidents	None recorded within 250m
Radon risk	 Less than 1% (Low risk – no protection measures) Moderate risk (Between 3% and 5%) identified in Northwest corner
UXO risk	Moderate risk area
Environmental Sensitive Land Uses	 London Green Belt On site Nitrate vulnerable Zone On site – LEE Surface water, Hatfield Groundwater Priority Habitat Inventory On site – Coastal and floodplain grazing marsh Batford Springs 153NW of site

3.4 Preliminary Risk Assessment

3.4.1 Identification of Critical Receptors

The identified potentially critical receptors are presented in Table 3.



Table 3 - Identification of Potential Receptors

Receptor Type	Current/Future	Receptor Details	Active
	Future	Residential receptors onsite	Yes
Human Health	Future	Construction workers onsite	Yes
	Current	Residential/commercial receptors offsite	Yes
	Current	Groundwater within aquifer	Yes
Controlled waters	Current	Groundwater within SPZ/licensed abstraction	Yes
	Current	Surface water body	Yes

The risks to onsite workers can be minimised by following appropriate health and safety guidance on site (i.e. wearing protective clothing and washing).

3.4.2 Identification of Potential Areas of Concern

The list of potential areas of concern on site and in the surrounding area are summarised in Table 4.

Table 4 - Identification of Potential Areas of Concern

Ref A of Con	Location	Potential Risk	Comments
Α	Onsite	Potentially imported made ground	Hydrocarbons (TPH, BTEX, PAH), heavy metals,
В	Onsite	Infilled land	inorganics, asbestos, cyanide, phenols, ground gas

The potential contaminants of PCBs arising from the electricity substation located offsite have been discounted as PCBs are not considered to be sufficiently mobile or soluble¹.

3.4.3 Identified Potential Pathways

Human Health Pathways

The potential human health exposure pathways for a residential receptor are indicated in Table 5.

21372R1 Issue A Page 5 May 2025

¹ Department of the Environment, 1996, Industry Profile: Engineering works. P.14 Sect 3.2.1



Table 5 - Identification of Potentially Active Human Health Exposure Pathways

Potential Pathway	Active/ Inactive	Notes
Ingestion of soil and dusts	Active	Qualitative Risk Assessment required.
Dermal contact with soils and dust	Active	Qualitative Risk Assessment required.
Ingestion of home grown produce	Active	Qualitative Risk Assessment required
Inhalation of dusts	Active	Qualitative Risk Assessment required
Inhalation of organic vapours (generated by shallow soils) in external areas or inside buildings	Active	Qualitative Risk Assessment required.
Inhalation of organic vapours generated by dissolved phase groundwater migrating offsite to neighbouring residential properties	Active	Qualitative Risk Assessment required.
Inhalation of organic vapours generated by dissolved phase groundwater migrating onto site from surrounding offsite sources	Active	Qualitative Risk Assessment required.
Contaminants from site entering groundwater and migrating into public water abstraction borehole for human consumption	Inactive	No potable abstractions within 500m. No further assessment necessary.

Controlled Waters Pathways

The potentially active controlled waters migration pathways are indicated in Table 6.

Table 6 - Identification of Potentially Active Controlled Water Pathways

Potential Pathway		Notes	
Impacted soils leaching to groundwater within Principal Aquifer	Active	Qualitative Risk Assessment required	
Impacted soils leaching to groundwater and migration to surface water	Active	Nearest surface water borders south of site. Qualitative Risk Assessment required.	

Ground Gas Pathways

The potential for ground gas risk depends on source-pathway-receptor linkages, with the age of infilling and type of waste as controlling factors. The potentially active migration pathways for ground gas are indicated in Table 7, along with a qualitative risk assessment.



Table 7 - Identification of Potentially Active Ground Gas Pathways

Potential Pathway	Active/ Inactive	Qualitative Risk Assessment	Notes	
Potential for natural materials with high organic content, such as peat (>4% TOC)	Inactive	Low	No indicated by geology. No further assessment required.	
Availability of readily degradable material, such as vegetable matter and food waste	Inactive	Low	No further assessment required.	
Nature of fill material - depth of fill >1m, incohesive materials, poorly compacted and within unsaturated zone.	Active	Low/Moderate	Further assessment required.	
Age of Materials - Ground gas generated from current/historical landfills <25yrs old	Inactive	Low	No landfills or mine workings recorded within 250m of site. No further assessment required.	
Distance from receptor – a higher distance reduces the potential risk for offsite migration. High risk generally limited to within 100m distance.	Active	Low/Moderate	Commercial and residential receptors within 150m of site.	
Presence of Preferential Pathways – fissures/fractures in bedrock or permeable strata beneath an impermeable cover	Active	Low/Moderate	Published bedrock geology is Lewes nodular chalk and Seaford chalk formation beneath Kesgrave catchment and Alluvium.	
Chemical storage/spillages with potential for hydrocarbon vapours	Inactive	Low	No further assessment required.	
Shallow or deep mine workings	Inactive	Low	No further assessment required.	
Radon gas protective measures required	Active	Low/Moderate	<1% (Low risk). Moderate risk (Between 3% and 5%) identified in Northwest Corner. Basic protective measures required.	

3.4.4 Qualitative Risk Assessment

A summary of the relevant pollutant linkages based on a source-pathway-receptors analysis is provided in Table 8.



Table 8 - Summary of Potentially Active Source-Pathway-Target Assessment

Sources	Potential Pathway	Potential Receptor	Risk Classification
	Dermal contact, outdoor and indoor inhalation, ingestion, homegrown produce	Human Health (Onsite Residential)	Low/Moderate
Onsite Sources (Potentially	Vapour inhalation from dissolved phase groundwater migrating from site to neighbouring properties	Human Health (Offsite Residential)	Low/Moderate
imported made ground)	Impacted soil leaching to groundwater within Principal Aquifer	Controlled Waters (Groundwater)	Low/Moderate
	Impacted soil leaching to groundwater and migration to surface water	Controlled Waters (Surface water)	Low/Moderate
Offsite Source (Industrial land uses)	Vapour inhalation from dissolved phase migration from offsite sources	Human Health (Onsite residential)	Low
Onsite Sources (Made ground)	Source for ground gas generation	Human Health (Onsite residential)	Low/Moderate
Radon sources	Source for radon gas from natural geology	Human Health (Onsite residential)	Low/moderate



4.0 PHASE II INVESTIGATION WORKS

4.1 Summary Of Works

The intrusive locations are detailed on Figure 4 and comprise the following:

4no. Trial Pits (TP1-TP4) were excavated to a maximum depth of 1.10m bgl for soakage testing.

All of the fieldwork was completed under the supervision of a WDE site engineer. Each location was scanned for underground services using a CAT/Genny prior to drilling. Soils were logged to British Standards by the supervising engineer.

4.2 Constraints/Selection of Intrusive Locations

Locations for intrusive investigation were provided by the client. Groundwater seepage encountered in:

- TP1.1 at 1.10m
- TP1.2 at 1.10m bgl
- TP2 1.10m bgl

Trial pits were terminated as soon as groundwater was encountered.

4.3 Field Results

4.3.1 Geology

The typical material/geology that was encountered during the intrusive works is summarised below in Table 9 and presented on the borehole logs in Appendix B.

Table 9 - Summary of Geology Proved Onsite

Units	Description	Min – Max Depth Base (m bgl)	Average Depth (m bgl)	Locations
Topsoil		0.20	0.00 - 0.20	All
Gravelly clay	Firm grey/brown gravelly clay	0.50+ – 1.10+	0.20 - 0.86+	All

4.3.2 Groundwater

Groundwater was encountered at 1.1m in TP1.1, TP1.2 and TP2.



4.3.3 Permeability Results

A summary of BRE365 soakage results is presented in Table 10 and in full in Appendix B.

Table 10 - Summary of BRE365 Soakage Testing

Location	Depth (m bgl)	Test Type	Strata	Drainage (m/sec) Test 1	Drainage (m/sec) Test 2	Drainage (m/sec) Test 3	Qualitative Soakage Potential
TP1.2	1.00	BRE365	Gravelly clay	1.18E-05	1.07E-05	8.33E-06	Moderate/Poor
TP2	1.00	BRE365	Gravelly clay	1.13E-05	6.93E-06	5.59E-06	Moderate/Poor
TP3	0.50	BRE365	Gravelly clay	9.09E-06	7.31E-06	7.10E-06	Poor
TP4	0.50	BRE365	Gravelly clay	8.01E-06	6.51E-06	3.64-06	Poor

The soakage testing indicates moderate to poor soakage rates. Groundwater was encountered at 1.10m bgl and therefore the site is not likely to be viable for shallow soakage's to ground.

A drainage engineer should be consulted further.

4.3.4 Revised Ground Gas Risk Assessment

An update to the ground gas risk assessment is presented in Table 11 which has incorporated the results obtained from this assessment.

Table 11 - Updated Ground Gas Risk Assessment

Identified Active Sources	Identified Active Potential Pathways	Potential Receptors	Quantitative Risk Assessment
No made ground encountered on site	No source	No source	Low

The revised ground gas risk assessment indicates a very low risk from ground gas (*Very Low/NHBC Green*).



Geo-Site Assessment Lower Luton Road, Harpenden Jarvis Strategic Land Ltd

5.0 RECOMMENDATIONS FOR FURTHER WORK

The site has been assessed to have a low/moderate risk to future receptors from contamination.


WDE recommends that the following items are undertaken:

- Preliminary UXO report due to the moderate UXO risk identified
- BGS Radon report due to the low/moderate risk identified
- Additional investigations are undertaken to confirm the foundation design.
- Site won materials are reused in line with CL:AIRE Code of Practice.






FIGURES



Job number: 21372 02/05/2025



Job number: 21372 02/05/2025





62A Western Road

HERTS

HP23 4BB

T: 01442 825570

E: general@wdeconsulting.co.uk


JARVIS HOMES

LOWER LUTON ROAD, HARPENDEN

FIGURE 3:PROPOSED SITE PLAN

Drawing supplied by client

02/05/2025 Job number: 21372



Job number: 21372 02/05/2025



APPENDIX A: RELEVANT GUIDANCE AND LEGISLATION

WDE Consulting has duly taken account of the recommendation contained within relevant guidance documents and legislation during the preparation of this report.

CONTAMINATION

Part IIa of the Environmental Protection Act 1990 defined contamination in relation to continued land use and introduced the "polluter pays" principal. The Groundwater Regulations 1998 defined List 1 and List 2 substances and the procedures for preventing them from entering groundwater. The Water Resources Act of 1991 introduced the term "controlled waters" and gave powers to the Environment Agency to require remediation where there was pollution of controlled waters.

The National Planning Policy Framework² requires the following:

- The site is made suitable for its intended use, taking account of all ground conditions arising
 from natural and former activities, pollution arising from previous uses and proposals for
 mitigation including land remediation.
- After remediation, as a minimum, land should not be capable of being determined as contaminated land under Part IIA of the Environmental Protection Ac 1990.
- Adequate site information, prepared by a competent person, is presented.

The methodology adopted for this report follows the guidance and procedures for Land Contamination Risk Management (LCRM) produced by the Agency³. The LCRM process provides a reasoned and structured mechanism to identify potential risk issues and, where necessary, provide a way forward to develop a robust risk management strategy to address potentially unacceptable risks in an appropriate manner. Contained within the LCRM Framework are the following stages:

- 1. Stage 1 risk assessment
- 2. Stage 2 options appraisal
- 3. Stage 3 remediation and verification

British Standards has issued guidance for the Investigation of Potentially Contaminated Sites⁴ and for undertaking Site Investigations⁵ which have duly been considered. An update to the potential human health exposure pathways is provided in the Environment Agency Soil Science Report SR3⁶. In 2008 the Environment Agency and the National House-Building Council (NHBC), Chartered Institute of Environmental Health (CIEH) released a joint publication for the Safe Development of Housing on Land

² Department of Communities and Local Government. March 2012

³ Environment Agency. 2020. Land Contamination Risk Management (LCRM)

 $^{^4}$ British Standards 2011. Investigation of Potentially Contaminated Sites-Codes of Practice. BS10175:2011

⁵ British Standards. 2015. Code of Practice for Site Investigations. BS5930

⁶ Environment Agency, August 2008, Updated technical background to the CLEA model, Science Report - SC050021/SR3



Affected by Contamination⁷. Guidance is provided in the CLR Report No 4 on sampling strategies for contaminated land⁸.

QUALITATIVE RISK ASSESSMENT

The potentially active human health are based on the Agency Soil Science Report SR3⁹. The potential contaminants of PCBs arising from the electricity substation located offsite have been discounted as PCBs are not considered to be sufficiently mobile or soluble¹⁰.

To assess the potential for risk, the Source $^{\circ}$ Pathway $^{\circ}$ Receptor relationships have been evaluated to determine whether there are potentially active pollutant linkages between sources and receptors. Only when there is an active pollutant linkage, can there be a potential risk to a receptor from a source via a particular pathway. Each active pathway has been assigned a qualitative assessment as to the level of risk as shown in the below table and as per R&D 66^7 .

Qualitative Risk Classification Scheme

		CONSEQUENCE									
		Severe	Medium	Mild	Minor						
	High likelihood	Very High Risk	High risk	Moderate risk	Low risk						
BILITY hood)	Likely	High risk	Moderate risk	Moderate/low risk	Low risk						
PROBABILITY (Likelihood)	Low likelihood Moderate risk		Moderate/low risk	Low risk	Very low risk						
	Unlikely	Moderate/low risk	Low risk	Very low risk	Very low risk						

GROUND GAS

The following relevant guidance will be used to assess the risks posed by ground gas:

- CIRIA Assessing risks posed by hazardous ground gases to buildings¹¹
- NHBC: Guidance on evaluation of development proposals on sites where methane and carbon dioxide are present¹²
- NHBC: Technical Extra¹³

⁷ Environment Agency. 2008. Guidance for the Safe Development of Housing on Land Affected by Contamination. R&D 66 8 DOE. 1994. Sampling Strategies for Contaminated Land. CLR Report No 4

⁹ Environment Agency, August 2008, Updated technical background to the CLEA model, Science Report - SC050021/SR3

¹⁰ Department of the Environment, 1996, Industry Profile: Engineering works. P.14 Sect 3.2.1

 $^{^{11}}$ CIRIA 2007. Assessing Risks Posed by Hazardous Ground Gases to Buildings. C665

 $^{^{12}}$ NHBC 2007. Guidance on Evaluation of Development Proposals on Sites where methane and carbon dioxide are present

¹³ NHBC 2016. Technical Extra. Ground Gas Update. April 2016. Issue 20



GROUNDED SOLUTIONS

- The Building Regulations Site Preparation and resistance to contaminants and moisture.
- British Standard. Guidance on Investigations for Ground Gas¹⁵
- NHBC guidance on Hazardous ground gas¹⁶

Summary of NHBC Traffic Light System

	М	ethane	Carbon Dioxide			
Gas Regime	Typical max %	Gas Screening Value (l/hr)	Typical max %	Gas Screening Value (l/hr)		
Green	<1	<0.16	<5	<0.78		
Amber 1	1 – 5	0.16 - 0.63	5 – 10	0.78 – 1.56		
Amber 2	5 – 20	0.63 – 1.56	10 – 30	1.56 – 3.13		
Red	20+	1.56+	30+	3.13+		

SOAKAGE TESTING AND DESIGN

The following guidance has been followed during the soakage testing:

- Falling Head Tests in boreholes BS5930⁵
- BRE Digest 365 2003 Soakage testing

The CIRIA publication¹⁷ provides guidance as to the required distance of buildings from soakage's to ground in chalk as follows:

- 20m distance of soakaways from buildings where dissolution features are known to be prevalent
- 10m distance of soakaways from buildings where chalk is low density or unknown
- 5m distance of soakaways from buildings where chalk is of medium to high density

 $^{^{14}}$ Building Regulations 2004. Approved Document C, Site Preparation and resistance to contaminants and moisture.

 $^{^{15}}$ British Standards 2013. Guidance on Investigation for Ground Gas. BS8576. 2013

 $^{^{16}}$ NHBC 2023. Hazardous Ground Gas – an essential guide for housebuilders. NF94

¹⁷ CIRIA. 2002. Engineering in Chalk. C574.



APPENDIX B: SITE PHOTOS



Photo 2 - TP2 East of Site





GROUNDED SOLUTIONS

Photo 3 - TP3 North of site



Photo 4 - TP2 Backfilled on completion







APPENDIX C: ENVIRONMENTAL DATABASE

Folder link: Appendix C - Environmental Database





APPENDIX D: FIELD LOGS





APPENDIX E: FIELD SHEETS

					Tria	l Pi	t							P1.1 eet 1 of 1
					Hole Type		Eastir	ng		Northing	(Ground Level (m)	Scale 1:25	
					Project Name					Project No.		Start Date	End Date	
Client					Lower Luton R	load, Harpen	Consi			21372		2025-04-09 Contractor	2025-04-09	
Jarvis				mples er	ad Tooto			otte Bird						
Inst/ Backfill	Nater evels	Depth (m)	Type/ Ref	mples an				Depth (thickness)			51	Pagarintian		
		Depth (m)	Řef		Results		(m)		Legend	TOPSOIL		Description		
								0.20						
									8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	Firm grey/brown sli rounded to angular	lightly grave r.	illy cobbly CLAY. G	Gravels are fine to co	oarse
									$a \sim 1$					0.5
								(0.90)						-
								(0.90)						-
									0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0					E
									@ 					1.0
								1.10			End o	f Trial Pit at 1.10m		
														-
														_ 1.5
														-
														-
														F
														-2.0
														-
														-
														L
														E
														3.0
														-
														— —3.5
														-
														-
														-4.0
														F
														-
														— —4.5
														-
														-
														5.0
Rema Grour		ter encount	ered at 1	1.10m				_				Method, Plant, Sta	ıbility, Dimensions	Logger

Trial Pit TP1.1 SUPPLEMENTARY INFO

Hole Type
TPEasting
TPNorthingGround Level (m)
1:25Scale
1:25Project Name
Lower Luton Road, HarpendenProject No.
21372Start Date
2025-04-09End Date
2025-04-09

Client Consultant Contractor
Jarvis Homes Charlotte Bird

Water Strike - General									
Struck (m)	Seal Depth (m)	Casing Depth (m)	Date and Time	Remarks					
1.10									

Remarks
Groundwater encountered at 1.10m

Method, Plant, Stability, Dimensions Logger

					Trial Pit								TP1	
				-	Hole Type TP		Easti	ng		Northing	(Ground Level (m)	Scale	1011
					Project Name					Project No.		Start Date	1:25 End Date	
Client					Lower Luton Ro	oad, Harpei	Cons	ultant		21372		2025-04-09 Contractor	2025-04-09	
Jarvis	Home		San	nples an	d Toete			otte Bird				rata		
Inst/ Backfill	Water evels	Depth (m)	Type/ Ref	iipies aii	Results		(m)	Depth (thickness) (m)	Legend		31	Description		
	_	Deptil (III)	Ref		Nesulis		()		Legend	TOPSOIL		Description		
								0.20	@ @					
										rounded to angular.	ghtly grave	elly cobbly CLAY. G	ravels are fine to coars	se _
														-0.5
								(0.90)						-
								(,	@_ &_					
									_ <u>~</u> _ o					-
								1.10	@ @ @ @ @					1.0
											End o	f Trial Pit at 1.10m		-
														-1.5
														L
														-
														-2.0
														-2.0
														-
														F
														-2.5
														F
														F
														-3.0
														-
														-
														-3.5
														-
														-4.0
														F
														- 4.5
														-
														L
														F
														-5.0
Rema Grour		ter encount	ered at 1	.10m								Method, Plant, Stal	bility, Dimensions	Logger
												I		

Trial Pit SUPPLEMENTARY INFO

Northing Ground Level (m)

Hole Type TP **Scale** 1:25 Easting Project Name Lower Luton Road, Harpenden Project No. 21372 Start Date 2025-04-09 End Date 2025-04-09 Consultant Charlotte Bird Contractor

Client Jarvis Homes				Consulta Charlotte		Contractor		
Water Strike - General								
Struck (m) Seal Depth (m)		Casing I	Casing Depth (m) Date and Time		Remarks			
	1.10							

Remarks
Groundwater encountered at 1.10m Method, Plant, Stability, Dimensions Logger

				Trial	Pit						P2
				Hole Type	Easti	ng		Northing	Ground Level (m)	Scale 1:25	
				Project Name Lower Luton Road	, Harpenden			Project No. 21372	Start Date 2025-04-09	End Date 2025-04-09	
Client Jarvis	Hom	es		,	Cons	ultant lotte Bird	d		Contractor		
Inst/	ter els	Depth (m)	San	ples and Tests	Level	Depth (thickness)			Strata		
ackfill	Le Wa	Depth (m)	Type/ Ref	Results	(m)	(m)	Legend	TOPSOIL	Description		
						0.20					
							\$ 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		htly gravelly cobbly CLAY. Gra	ivels are fine to coa	arse
											-0.5
						(0.90)	100 a				F
							6 6 0 8 0 0				
											1.0
						1.10			End of Trial Pit at 1.10m		
											-1.5
											-2.0
											F
											2.5
											-3.0
											E
											-3.5
											E
											-4.0
											Ė
											L
											-4.5
											F
											-5.0
Rema Groun		ter encount	ered at 1.	10m					Method, Plant, Stabi 0.00 - 1.00m TP Stable	lity, Dimensions	Logger CNE
									L = 2.00m $W = 0.70$)m	

Trial Pit SUPPLEMENTARY INFO Hole Type TP Easting Northing Ground Level (m) Scale Project Name Lower Luton Road, Harpenden Project No. 21372 Start Date 2025-04-09 End Date 2025-04-09 Client Jarvis Homes Consultant Charlotte Bird Contractor Water Strike - General Seal Depth (m) Casing Depth (m) Date and Time Remarks 1.10 Method, Plant, Stability, Dimensions Logger

Groundwater encountered at 1.10m

0.00 - 1.00m TP Stable L = 2.00m

W = 0.70m


					Trial	Pit							TF	
				-	Hole Type TP	Ea	sting		Northing	(Ground Level (m)	Scale 1:25		
					Project Name Lower Luton Road	d Harpenden			Project No. 21372		Start Date 2025-04-09	End Date 2025-04	e -09	
Client Jarvis	Home	es				Co	nsultant arlotte Bi	rd	-		Contractor			
				nples an	d Tests		el Depti			St	rata			
Backfill	Wa	Depth (m)	Type/ Ref		Results	(m		Legend			Description			
							(0.20)		TOPSOIL					-
							0.20	0-0-	Firm orange/brow subangular.	n gravelly Cl	LAY. Gravels are f	ine to medium	rounded to	-
							(0.30)	0_0_						0.5
							0.50			End of	f Trial Pit at 0.50m			- 0.0
														-
														1.0
														-
														—1.5 —
														-
														F
														2.0
														-
														-2.5
														F
														-3.0
														-3.5
														-
														4.0
														-
														4.5
														-
														F
														-5.0
Remai											Method, Plant, Sta	ability, Dimensi	ions	Logger
Grour	ndwat	er not enco	ountered								0.00 - 0.50m TP Stable L = 2.00m W = 0			CNB


					Trial	Pit							TF	
				-	Hole Type TP	Eas	ting		Northing	(Ground Level (m)	Scale 1:25		-
					Project Name Lower Luton Road	Harpenden			Project No. 21372		Start Date 2025-04-09	End Date 2025-04	e -09	
Client Jarvis	Home	es		ı		Cor	sultant Irlotte Bir	d	-		Contractor			
			San	nples an	nd Tests		el Depth (thickness)			St	rata			
Backfill	Wa	Depth (m)	Type/ Ref		Results	(m		Legend			Description			
							(0.20)		TOPSOIL					_
							0.20	0-0-	Firm orange/brow subangular.	vn gravelly Cl	LAY. Gravels are f	ine to medium	rounded to	<u> </u>
							0.50	000						0.5
							0.30			End of	f Trial Pit at 0.50m			-
														-
														—1.0 —
														-
														—1.5 —
														2.0
														-
														2.5
														-3.0
														-3.5
														_
														-4.0
														-
														_ 4.5
														_
														F
														-5.0
Remai											Method, Plant, Sta	ability, Dimens	ions	Logger
Grour	ndwat	er not enco	ountered								0.00 - 0.50m TP Stable L = 2.20m W = 0			CNB



Location	TP1 (Fill 1)
Length (m)	2.1
Width (m)	0.7
Depth (m)	1
Surface Area (m²)	7.07
Depth of Water Lost (m)	0.21
Effective Storage Volume (Vp75-Vp25)	0.15435

Time (s)	Depth to Water (m)
0	-0.5
60	-0.5
90	-0.51
120	-0.51
3900	-0.55
5220	-0.59
7380	-0.61
9780	-0.64
12300	-0.71





Vp	Amount of Water Lost	DTW bgl
75%	0.1575	-0.5525
25%	0.0525	-0.6575

Soil Infiltration Rate (m/sec)


1.18E-05


Job No 21372 TP1 (Fill 1)



Location	TP1 (Fill 2)
Length (m)	2.1
Width (m)	0.7
Depth (m)	1
Surface Area (m²)	7.07
Depth of Water Lost (m)	0.23
Effective Storage Volume (Vp75-Vp25)	0.16905

-: / \	5 4 4 4 4 4 4 4
Time (s)	Depth to Water (m)
0	-0.48
90	-0.52
4400	-0.54
6400	-0.58
8600	-0.6
11000	-0.63
13000	-0.67
15000	-0.71
	İ
	İ





Vp	Amount of Water Lost	DTW bgl
75%	0.1725	-0.5375
25%	0.0575	-0.6525

Soil Infiltration Rate (m/sec)

1.07E-05


Job No 21372 TP1 (Fill 2)



Location	TP1 (Fill 3)
Length (m)	2.1
Width (m)	0.7
Depth (m)	1
Surface Area (m²)	7.07
Depth of Water Lost (m)	0.15
Effective Storage Volume (Vp75-Vp25)	0.11025

Time (s)	Depth to Water (m)
0	-0.48
560	-0.5
1400	-0.52
5600	-0.54
8000	-0.58
9800	-0.61
11000	-0.63
	İ





Vp	Amount of Water Lost	DTW bgl
75%	0.1125	-0.5175
25%	0.0375	-0.5925

Soil Infiltration Rate (m/sec)


8.33E-06


Job No 21372 TP1 (Fill 3)



Location	TP2 (Fill 1)	
Length (m)	2	
Width (m)	0.7	
Depth (m)	1	
Surface Area (m²)	6.8	
Depth of Water Lost (m)	0.11	
Effective Storage Volume (Vp75-Vp25)	0.077	

Time (s)	Depth to Water (m)
0	-0.6
120	-0.6
300	-0.61
2880	-0.62
4380	-0.63
6,600	-0.66
8760	-0.69
11220	-0.71
	İ
	İ
	İ
	İ





Vp	Amount of Water Lost	DTW bgl
75%	0.0825	-0.6275
25%	0.0275	-0.6825

Soil Infiltration Rate (m/sec)

1.13E-05


Job No 21372 TP2 (Fill 1)



Location	TP2 (Fill 2)	
Length (m)	2	
Width (m)	0.7	
Depth (m)	1	
Surface Area (m²)	6.8	
Depth of Water Lost (m)	0.08	
Effective Storage Volume (Vp75-Vp25)	0.056	

Time (s)	Depth to Water (m)
0	-0.6
480	-0.61
3500	-0.62
6000	-0.64
7500	-0.65
10000	-0.68





Vp	Amount of Water Lost	DTW bgl
75%	0.06	-0.62
25%	0.02	-0.66

Soil Infiltration Rate (m/sec)


6.93E-06


Job No 21372 TP2 (Fill 2)



Location	TP2 (Fill 3)	
Length (m)	2	
Width (m)	0.7	
Depth (m)	1	
Surface Area (m²)	6.8	
Depth of Water Lost (m)	0.1	
Effective Storage Volume	0.07	
(Vp75-Vp25)	0.07	

Time (s)	Depth to Water (m)
0	-0.65
4000	-0.67
6700	-0.71
12000	-0.73
14000	-0.75
11000	0.75
	_
	i
	+
	-





Vp	Amount of Water Lost	DTW bgl
75%	0.075	-0.675
25%	0.025	-0.725

Soil Infiltration Rate (m/sec)

5.59E-06


Job No 21372 TP2 (Fill 3)



Location	TP3 (Fill 1)	
Length (m)	2	
Width (m)	0.7	
Depth (m)	0.5	
Surface Area (m²)	4.1	
Depth of Water Added (m)	0.28	
Effective Storage Volume (Vp75-Vp25)	0.196	

Time (s)	Depth to Water (m)
0	-0.22
1740	-0.28
3900	-0.36
5880	-0.38
7,380	-0.39
9380	-0.4
12000	-0.43
	İ
	İ
	İ





Vp	Amount of Water Lost	DTW bgl
75%	0.21	-0.29
25%	0.07	-0.43

Soil Infiltration Rate (m/sec)


9.09E-06


Job No 21372 TP3 (Fill 1)



Location	TP3 (Fill 2)
Length (m)	2
Width (m)	0.7
Depth (m)	0.5
Surface Area (m²)	4.1
Depth of Water Added (m)	0.3
Effective Storage Volume (Vp75-Vp25)	0.21

Time (s)	Depth to Water (m)
0	-0.2
2000	-0.25
4500	-0.28
7000	-0.35
9,000	-0.37
11000	-0.39
14000	-0.4
17000	-0.43





Vp	Amount of Water Lost	DTW bgl
75%	0.225	-0.275
25%	0.075	-0.425

Soil Infiltration Rate (m/sec)

7.31E-06


Job No 21372 TP3 (Fill 2)



Location	TP3 (Fill 3)	
Length (m)	2	
Width (m)	0.7	
Depth (m)	0.5	
Surface Area (m²)	4.1	
Depth of Water Added (m)	0.27	
Effective Storage Volume (Vp75-Vp25)	0.189	

Time (s)	Depth to Water (m)	
0	-0.23	
5000	-0.29	
8800	-0.34	
10500	-0.36	
13,000	-0.39	
17000	-0.43	
19000	-0.44	





Vp	Amount of Water Lost	DTW bgl
75%	0.2025	-0.2975
25%	0.0675	-0.4325

Soil Infiltration Rate (m/sec)


7.10E-06


Job No 21372 TP3 (Fill 3)



Location	TP4 (Fill 1)	
Length (m)	2.2	
Width (m)	0.7	
Depth (m)	0.5	
Surface Area (m²)	4.44	
Depth of Water Lost (m)	0.1	
Effective Storage Volume (Vp75-Vp25)	0.077	

Time (s)	Depth to Water (m)
0	-0.23
60	-0.23
300	-0.24
2160	-0.26
4,440	-0.27
6180	-0.29
8700	-0.33





Vp	Amount of Water Lost	DTW bgl
75%	0.075	-0.255
25%	0.025	-0.305

Soil Infiltration Rate (m/sec)

8.01E-06


Job No 21372 TP4 (Fill 1)



Location	TP4 (Fill 2)	
Length (m)	2.2	
Width (m)	0.7	
Depth (m)	0.5	
Surface Area (m²)	4.44	
Depth of Water Lost (m)	0.11	
Effective Storage Volume	0.0847	
(Vp75-Vp25)	0.0047	

Time (s)	Depth to Water (m)	
0	-0.21	
2200	-0.25	
4500	-0.26	
6700	-0.28	
9,500	-0.3	
11500	-0.32	





Vp	Amount of Water Lost	DTW bgl
75%	0.0825	-0.2375
25%	0.0275	-0.2925

Soil Infiltration Rate (m/sec)


6.51E-06


Job No 21372 TP4 (Fill 2)



Location	TP4 (Fill 3)
Length (m)	2.2
Width (m)	0.7
Depth (m)	0.5
Surface Area (m²)	4.44
Depth of Water Lost (m)	0.11
Effective Storage Volume (Vp75-Vp25)	0.0847

Time (s)	Depth to Water (m)
0	-0.24
1200	-0.27
3000	-0.29
6500	-0.31
10,000	-0.32
14000	-0.35





Vp	Amount of Water Lost	DTW bgl
75%	0.0825	-0.2675
25%	0.0275	-0.3225

Soil Infiltration Rate (m/sec)

3.64E-06

Job No 21372 TP4 (Fill 3)

WDE RANGE OF SERVICES

Phase 1 Desk Studies

Geo-Environmental Assessments

Geo-Site Assessments

Remedial Strategies and DQRAs

Soakage Testing: BRE365 and borehole permeability testing

Remedial Verification & Closure Reports

Environmental Monitoring Programmes

Material Management Plans (MMP)

Construction Environmental Management Plans (CEMP)

Site Waste Management Plans on construction sites

Developing sustainable waste strategies

UR SERVICES

21372R1 Issue A May 2025



Lucion Ground Engineering Limited

Newark Road Peterborough PE1 5UA Registered in England No 6929574 01733 566566 geadmin@luciongroup.com

EXPLORATORY HOLE RECORDS LOWER LUTON ROAD HARPENDEN

Report Reference No. 136262


On behalf of: -

Jarvis Homes Limited

Burgundy House 21 The Foresters Harpenden AL5 2FB

July 2025

Exploratory Hole Location Plan Reproduced from a plan provided by the client.



Project : Lower Luton Road, Harpenden

Client: Jarvis Homes Limited



Project No. **LUCION GROUND ENGINEERING LIMITED**

Peterborough Tel: 01733 566566 136262



Site: Lower Luton Road, Harpenden

WINDOW SAMPLE WS01

Peterborough Tel: 01733 566566

23/07/2025 Final Depth Equipment
4.00 m Dynamic Sampling Rig

Peterborough	Tel : 017	33 566566	23/01/2	.020	4.00 m	Dynamic Sampling Rig		
Sample and In Situ Testing		Water Levels (Casing)	Well		Legend	Depth (m)		
0.20	Type D1	Results			MADE GROUND -	Brown, silty, gravelly SAND. Gravel of flint.		
0.50	D2				MADE GROUND - flint and plastic.	Dark brown, slightly gravelly, sandy SILT. Grave	el of	0.30
0.80	D3		_		Firm, becoming so slightly sandy, sligl angular flint.	oft, then very soft, brown, orange brown and grey, htly gravelly, silty CLAY. Gravel of angular to sub		0.70
1.20 1.20-2.00 1.35-1.65	D4 U1 CPT	N0 (1/0,0,0,0	0) cw <u>▼</u>		Very soft, light gre	y, silty, slightly organic CLAY.		1.25
						thickly laminated, light grey and off-white, clayey aty root fragments.	SILT X X X X X X X X X X X X X X X X X X	1.50
2.00 2.00-3.00 2.15-2.45	D5 U2 SPT	N8 (3/2,3,1,2	(2.00)		Firm, brown and go to rounded flint and Medium dense, ora	wn, clayey, pseudofibrous PEAT. rey, slightly sandy, gravelly CLAY. Gravel of ango d chalk. ange brown and light brown, slightly clayey, sand of angular to sub-rounded flint.	× 0 0 0 %	1.95 2.05 2.15
3.00-4.00 3.15-3.45	U3 CPT	N13 (6/4,4,2,	C ▼ 2.30 (3.00)					
4.15-4.45	СРТ	N15 (4/4,4,4,	3) 2.75			End of Borehole at 4.00m	**************************************	4.00
Remarks . Starter pit ex . Borehole cas		to 1.20m depth				Hole Diameter by Depth (m) Diamet	— Projec	

3. Gas monitoring standpipe installed to 4.00m depth.

4.00 87 1362 Scale: 1:25

le: Page 5 1/1

KEY			Groundwater Strike				Groundwater Observations			
D - Disturbed Sample	MP - Mackintosh Probe	Strike (m	Rose To (m)	Casing (m)	Sealed	Remarks	Date	Depth (m)	Casing (m)	Water (m)
B - Bulk Sample	V - Vane Shear Test	2.30	2.30	2.00	Not	Fast	23/07/2025		4.00	2.75
U - Undisurbed Sample W - Water Sample	N/* - SPT Blows ES - Environmental Sample						23/07/2025	4.00		1.05
S/C - SPT Spoon/Cone	▼ - Level On Completion									
	▼ - Level Casing Withdrawn									
▼- Water Rise	▼ - Standpipe Level									



WINDOW SAMPLE

Site: Lower Luton Road, Harpenden **WS02** LUCION GROUND ENGINEERING LTD. Final Depth Equipment 23/07/2025 Tel: 01733 566566 Peterborough 4.45 m Dynamic Sampling Rig Water Levels (Casing) Sample and In Situ Testing Depth Well Stratum Description Legend (m) Depth (m) Type Results MADE GROUND - Light brown, silty, gravelly SAND. Gravel of flint and 0.10 D4 brick. 0.30 D₁ 0.40 Very stiff, becoming firm, brown and orange brown, slightly gravelly, silty CLAY. Gravel of angular to sub-rounded flint. 0.60 D2 0.90 D3 1.20 D5 1.20-2.00 U1 N5 (3/0,1,2,2) 1.35-1.65 SPT 1.45 Structureless CHALK of firm, off-white and white, gravelly SILT with occasional firm, brown clay partings. Gravel of angular to sub-angular, very weak to weak, low density chalk clasts, and occasional coarse gravel size flint nodules. 2.00 D6 (2.00)2.00-3.00 U2 2.15-2.45 SPT N72 (23/30, 24, 13, 5)3.00 D7 (2.00)3.00-4.00 U3 N13 (7/6,3,2,2) 3.15-3.45 SPT ...with iron staining on chalk clasts below 3.70m depth. 4.00 D8 (2.00) 4.15-4.45 N13 (7/2,3,5,3) SPT c ▼ 4.45 End of Borehole at 4.45m Remarks Hole Diameter by Depth Project No. 1. Starter pit excavated to 1.20m depth. Depth (m) Diameter (mm) 136262 2. Borehole cased to 2.00m depth. 2.00 87 3. Gas monitoring standpipe installed to 4.00m depth. 77 Page Scale: 67 4.00 1:25 1/1 KEY Groundwater Strike **Groundwater Observations** D - Disturbed Sample MP - Mackintosh Probe Strike (m) Rose To (m) Casing (m) Sealed Remarks Depth (m) Casing (m) Water (m) B - Bulk Sample V - Vane Shear Test 23/07/2025 3.70 4.00 2.00 Not Slow 4.45 2.00 4.20 U - Undisurbed Sample N/* - SPT Blows W - Water Sample ES - Environmental Sample

▼ - Level On Completion

▼ - Standpipe Level

▼ - Level Casing Withdrawn

S/C - SPT Spoon/Cone

▼- Water Rise



Appendix B

